



AOPEN

Bright Ideas Connected

C-Tile



C-Tile 19

Powered by the Chromebox Mini

A 19" 2-in-1 solution, which combines the Chromebox Mini with a touch display. This interactive solution is perfect for smart kiosks, room booking or check-in systems in different environments, such as retail, enterprises and schools. By integrating the Chromebox Mini and the screen, no extra cables are needed, which ensures a tamperproof solution for commercial environments.

C-Tile 19 features:

- Rockchip RK3288C Quad Core Cortex-A17 1.8GHz
- 19,5", 1920 x 1080 px, 250 nits, VA panel
- Fanless and solid-state
- Two-in-one solution



C-Tile



Model name		C-Tile 19
Feature		19" 2-in-1 solution, powered by the Chromebox Mini
Housing Material		Metal
Dimensions	W x H x D (mm)	492.6 x 306.6 x 40.8 mm
	W x H x D (inch)	19.4 x 12.1 x 1.6 inch
Weight		5.45kg / 12.21 lbs
WatchDog Timer		-
CPU		Rockchip RK3288C Quad Core Cortex-A17 1.8 GHz
Memory		Dual Channel, LPDDR3 1066,MHz, 4GB (on board)
Graphics	Chip	ARM Mali-T764
Panel	Resolution	19,5", 1920 x 1080
	Maximum Brightness	250 nits
	Panel Type	VA
	Viewing angle	178/178
	Response time	25ms
	Touch	Multi Touch PCT
Expansion slot		-
Audio	Type	Maxim MX98090
	Channel	Stereo
LAN		Gigabit 10/100/1000
Storage		EMMC 16G SSD (on board)
Security		Kensington Lock Hole x 1

System I/O	DC Jack	x 1	
	HDMI Port	-	
	USB 2.0 Port	x 4	
	RJ45 LAN Jack	x 1	
	COM PORT	RJ50 x 2	
	Audio Set	Line-Out	-
		Mic-in	-
	WiFi Antenna port	Embedded + Punch out for external antenna	
IP Grade		IP65	
Adapter		40W/19V	
Input Voltage		AC 100 ~ 240V	
Environment			
MTBF		50,000 hrs	
Operating Temperature		0 ~ 40°C	
Storage Temperature		-10 ~ 60°C	
Relative Humidity		90% RH (40°C non-condensing)	

Supports:



The specifications depicted may be subject to change without prior notice. All trademarks are copyright of their respective owners. © AOPEN Inc. Chrome, Chromebox and Chromebase are Registered trademarks of Google Inc.