




AOPEN

Bright Ideas Connected

eTILE



Commercial all-in-one Fanless, Slim & Robust for Kiosk **eTILE 15M-FP2**

AOPEN eTILE 15M-FP2 is a slim and commercial all-in-one interactive touch display for Kiosk applications. With the AiCU an Intelligent Device. Management Service Ready, its Cloud service through out-of-band control in Intel SoC platform. Frame protection design for IK compliance with metal chassis design, hidden keypad, IP compliance dust and water-proof and Full HD panel can be fully utilized in your self-Kiosk enclosure or commercial counter-table mounted applications.

The eTILE 15M-FP2 features:

- + Fanless design
- + HEVC/H.265 and extended power switch
- + Metal chassis for embedded structure with IK07 and IP65 grade front panel, an IPX2 rear panel and 7H hardness
- + Bezel to avoid a cracked screens

eTILE 15M-FP2



| Model name | | eTILE 15M-FP2 |
|------------------|------------------|--|
| Housing Material | | IP Metal Design |
| Dimension | W x H x D (mm) | 397.1 x 246.6 x 36.15 mm |
| | W x H x D (inch) | 15.63 x 9.71 x 1.42 inch |
| Weight | | 3.2 kg / 1.63 lbs |
| CPU | | Intel® Celeron® Processor J3455 (Quad Core) |
| Chipset | | CPU built-in |
| Memory | Channel | Dual Channel |
| | Type | DDR3L SO-DIMM x 2 |
| | Data Rate | 1866 MHz |
| | Memory | 2GB x 2 |
| Graphics | | Intel® HD Graphics 500 / 505 |
| Front Panel | Resolution | 15.6" 1920 x 1080 (16:9) |
| | Max Brightness | 250 NITS |
| | Panel Type | Vertical Alignment |
| | Viewing Angle | 178 / 178 |
| | Response Time | 25ms |
| | Contrast Ratio | 1000:1 |
| | Touch | PCT supports 10 points |
| Expansion slot | | M.2 2242 key B for SSD, M.2 2242 key B for AiCU/LTE/SSD, M.2 2230 key E for wifi |
| Audio | Type | Realtek HD Audio Codec ALC269 |
| | Channel | 2 Channel |
| LAN | | Realtek RTL8111G 10 / 100 / 1000 Mbps |
| Storage | | M.2 2242 (Default 64GB) |
| Security | | Hidden Keypad, Secure Cable Cover |

| Storage Bay | | - | |
|-----------------------|-----------------|--|-----|
| Front Camera | | - | |
| Side Panel I/O | Power Button | x 1 | |
| | Brightness Up | x 1 | |
| | Brightness Down | x 1 | |
| | HDD indicator | x 1 | |
| System Panel I/O | DC Jack | x 1 (12 ~ 19V) | |
| | HDMI Out Port | x 1 | |
| | USB 2.0 Port | - | |
| | USB 3.0 Port | x 4 | |
| | COM Port | x 1 (RJ450) | |
| | Audio Set | Line-Out | x 1 |
| | | Mic-in | x 1 |
| | AiCU Remote LAN | Optional x 1 | |
| | RJ45 LAN | x 1 | |
| | Others | Embedded WiFi Antenna x 2, Extended Power Switch x 1 | |
| Watchdog Timer | | 1 ~ 255 SEC./min | |
| IP/IK Grade | | IP65 / IK07 (Front), IPX2 (Rear) | |
| Adapter | | 90W (19V, 4.74A) AC Adapter | |
| Input Voltage | | AC 100 ~ 240V | |
| Warranty | | 2 Years | |
| TPM | | 2.0 | |
| Environment | | | |
| MTBF | | 50.000 hrs | |
| Operating Temperature | | 0 ~ 40°C (32 ~ 104°F) | |
| Storage Temperature | | -20 ~ 60 °C (-4 ~ 140°F) | |
| Relative Humidity | | 90% RH (40°C Non-Condensing) | |

Supports:



The specifications depicted may be subject to change without prior notice. All trademarks are copyright of their respective owners. © AOPEN Inc.