



Slim and Robust

Commercial All-In-One Touch

eTILE15312

AOPEN eTILE15312 is a slim, commercial all-in-one interactive touch display designed for kiosk applications. It features a 10-point multi-touch screen for smooth, responsive interaction. The device adopts an IPR (Interfered Protection Resin) design for IK07 compliance, combined with a durable metal chassis for a robust embedded structure. A hidden keypad, IP65-rated dust- and water-proof protection, and a 1920×1080 (FHD) panel make it a reliable choice for demanding kiosk enclosure applications.

The eTILE15312 features:

- Powered by Intel® Alder Lake-N processor
- Fanless design
- Support 10-point touch
- Metal chassis with IK07 and IP65 grade front panel protection
- Multiple I/O ports: USB 3.2 and RS232 for enhanced expandability
- FHD resolution with a wide viewing angle



eTILE15312



Model name		eTILE15312
Housing Material		Metal
Dimension	W x H x D (mm)	397.1 x 246.6 x 37 mm
	W x H x D (inch)	15.63 x 9.71 x 1.46 inch
Weight		3.2 kgs/7.06 lbs
CPU		N100/i3-N300
Chipset		CPU Build-in
Memory	Channel	Dual Channel
	Type	DDR5 SO-DIMM x 1
	Data rate	4800 MHz
	Max Memory	16GB (default 8G x1)
Graphics		Intel® HD Graphics
Resolution		1920 x 1080 (16:9)
Max Brightness		250 nits
Panel Type		TFT (Thin Film Transistors)
View Angle (CR>10)		178°/178°
Response time		25ms
Contrast Ratio		1000:1
Touch		PCT support 10 points
Expansion Slot		1 x M.2 (Key M, 2280) for SSD 1 x M.2 (Key E, 2230) for wifi 1 x M.2 (Key B, 2242) for LTE
Audio		Realtek ALC256 2 Channel
LAN		Intel® I226V with 10/100/1000/2500 Mbps

Storage		M.2 128G SSG
Storage Bay		-
Front Camera		5M webcam (optional)
Side Panel I/O	Power Button	x 1
	Brightness Up	x 1
	Brightness Down	x 1
	HDD Indicator	x 1
System I/O	DC Jack	x 1
	HDMI Out Port	x 1
	USB 2.0 Port	x 2
	USB 3.2 Port	x 2
	RS232 Serial Port	x 1
	Audio Set	Line-out x 1
		Mic-in x 1
	AiCU I/O	N/A
	Others	N/A
Watchdog Timer		1 ~ 255 SEC./min
IP Level / IK Level compliance		Front Panel IP65/IPX2/IK07
Adapter		90W (19V, 4.74A) AC Adapter
Input Voltage		AC 100 ~ 240V
Environment		
MTBF		50,000hrs
Operating Temperature		0 ~40°C (32 ~ 104°F)
Storage Temperature		-20 ~ 60°C (-4 ~ 140°F)
Relative Humidity		90% RH (40°C non-Condensing)



Windows 10 IoT or above



AOPEN Headquarter
New Taipei City,
Taiwan

AOPEN America
San Jose,
USA

AOPEN Europe
Rosmalen,
Netherland

AOPEN Australia
Melbourne,
Australia

AOPEN Japan
Tokyo,
Japan

AOPEN China
Shanghai,
China

v1.0